

**Rail Services International
Austria GmbH**
Domaniggasse 2, A-1100 Wien

T: +43 (0)1 617 77 71
F: +43 (0)1 617 77 71-28
E: info@railsi.at
www.railsi.at

Item description

Electrically monitored and activated StatX fire suppression generator Stat-X 250ME

Type	Art.No.
SX15530	59.760.84
Technical data	
Activation mechanism	electrical (6 – 24 VDC at 2,0 – 0,5A)
Trigger time	min. 50 ms
Connection (more than 1)	parallel: min. 0,5 A series: min. 1,0 A
Activation	heating element with 0,8 – 3.0 Ohm
Supervisory current	max. 5mA (permanent)
Test current	max. 25 mA (short term)
Gross weight	1370 grams
Aerosol mass	250 grams
Discharge time	18.0 sec.
Exhaust port	1
Exhaust length	2,00 meters
Min. mounting distance	0,95 meters
Dimensions	205 mm x 76 mm (diameter)
Fire class	A, B, C



Maximal protection volume per unit

Fire class A	2.58 m ³
Fire class B	3.73 m ³
Fire class C	5.21 m ³

Range of application:

Rooms	server cabinets, double floors
Transport	passenger cars, trucks, trains, metro
Storage	cabinets, safes
Large switch cabinets	control cabinets
Industry	transformers (large)